



SMIV Solid State Amplifiers

400 – 1000 MHz • 10 Watts to 5000 Watts, Minimum Rated Power

Instruments for Industry, SMIV-Series Amplifiers provide outstanding RF performance. These products are available in a wide range of power levels from 10 watts to 5000 watts in the 400 – 1000MHz frequency range. These state-of-the-art solid-state power amplifiers are specifically designed for laboratory and all testing applications.

IFI RF amplifiers are very conservatively designed to operate below maximum ratings for ruggedness and long term reliability. Sixth generation LD MOS Transistors provide reliable brute-power performance at frequencies up to 1000MHz.

Our RF power amplifiers feature heavy-duty individually shielded aluminum housings at the module level. This concept of a shielded modular design minimizes internally produced EMI signal leakage and provides easy access for field service and rapid turnaround at depot level repair facilities.

From the ground up, the “SMIV-SERIES” products are structurally engineered to withstand operation in mechanically hostile environments. Ruggedized versions are available for applications that will be exposed to very harsh environments.

Features

- Solid State Design
- Rugged Construction & High Reliability
- Instantaneous Broadband Frequency range
- Backlit screen
- Modular Design Construction
- Integrated Force Air Cooling
- Self-diagnostic circuitry
- IEEE-488 interface & RS232 Remote



Models & General Specifications

Model Number	Frequency Range (MHz)	Rated Power (Watts) Minimum	P1dB Power Watts Minimum	Gain (dB) Minimum	KVA	Weight In Pounds	Size In Inches
SMIV10	400-1000	10	10	40	.1KVA	25 Lbs	5.25" H x 19" W x 24" D
SMIV25	400-1000	25	25	44	.2KVA	28 Lbs	5.25" H x 19" W x 24" D
SMIV50	400-1000	50	50	47	.4KVA	32 Lbs	5.25" H x 19" W x 24" D
SMIV100	400-1000	100	80	50	.5KVA	36 Lbs	7.0" H x 19" W x 25" D
SMIV150	400-1000	150	120	52	.8KVA	40 Lbs	7.0" H x 19" W x 25" D
SMIV200	400-1000	200	160	53	1.4KVA	50 Lbs	7.0" H x 19" W x 25" D
SMIV250	400-1000	250	200	54	1.6KVA	60 Lbs	7.0" H x 19" W x 25" D
SMIV350	400-1000	350	250	56	3.0KVA	80 Lbs	8.75" H x 19" W x 25" D
SMIV500	400-1000	500	350	57	4.0KVA	120 Lbs	8.75" H x 19" W x 24" D
SMIV1000	400-1000	1000	800	60	8.0KVA	250 Lbs	2x 10.5" H x 19" W x 25" D
SMIV2000	400-1000	2000	1600	63	15.0KVA	500 Lbs	Rack Integrated
SMIV3000	400-1000	3000	2500	65	20.0KVA	700 Lbs	Rack Integrated
SMIV5000	400-1000	5000	4500	67	30.0KVA	1000 Lbs	Rack Integrated



SMIV Solid State Amplifiers

400 – 1000 MHz • 10 Watts to 5000 Watts, Minimum Rated Power

Standard Features for IFI SMIV Solid State Series Amplifiers

Table with 2 columns: Standard Features and Description. Features include VSWR protection, remote control, gain control, and safety interlocks.

IFI SMIV Solid State Series Amplifier Specifications

Table with 2 columns: Specification and Value. Includes frequency range, power ratings, impedance, VSWR, temperature, humidity, and modulation details.

Standard Prime Powers:

Table listing standard prime power options: 100, 115, 120 VAC; 220, 230, 240 VAC; and three-phase options.

Some Available Options for IFI SMIV Solid State Series Amplifiers

Table listing optional features such as remote control (Option 110-1E, 110-2, 110-3), rack mounting (Option 113), and RF input/output configurations (Options 118A, 118B).




SMIV Solid State Amplifiers


400 – 1000 MHz • 10 Watts to 5000 Watts, Minimum Rated Power

Outline Configurations:


5.25" High Chassis




7.0" High Chassis




8.75" High Chassis



10.5" Drawer Chassis



2x 10.5" Drawer Chassis Configuration





SMIV Solid State Amplifiers

400 – 1000 MHz • 10 Watts to 5000 Watts, Minimum Rated Power

Rack Outline Configurations:

